



**250 SILENCER TECHNICAL SPECS**

**STEP 1 : BAFFLE SELECTION (See Guide on Next Page)**

Size	Tick to Select	Quantity
<b>7mm</b> : Projectile aperture in baffle (0.243 max)		
<b>8mm</b> : Projectile aperture in baffle (0.277 max)		
<b>9mm</b> : Projectile aperture in baffle (0.308 max)		

**STEP 2 : BARREL CONNECTOR SELECTION**

Size	Tick to Select	Quantity
<b>M13 X 1</b>		
<b>M14 X 1</b>		
<b>M16 X 1</b>		
<b>M18 X 1</b>		
<b>1/2" 28TPI</b>		
<b>5/8" 24TPI</b>		
<b>9/16 24TPI LH</b>		
<b>M14 X LH</b>		

**STEP 3 : CONFIRM SELECTION**

Name & Surname	
Cell Number	
Email	
Date	
Signature	



## 250 SILENCER TECHNICAL SPECS

<b>CALIBER &amp; RECOMMENDED BAFFLE SIZE CHART</b>			
<b>Calibre</b>	<b>Size "</b>	<b>Size mm</b>	<b>Recommended Baffle</b>
.22-250 Rem*	0.224	5.6896	7mm
.220 Swift*	0.224	5.6896	7mm
.222 Rem*	0.224	5.6896	7mm
.223 Rem	0.224	5.6896	7mm
.243 Win	0.243	6.1722	7mm
6 x 45mm	0.243	6.1722	7mm
.25-06 Rem	0.257	6.5278	8mm
6.5 x 55 Swed	0.264	6.7056	8mm
.270 Win	0.277	7.0358	8mm
7 x 57 Mauser	0.284	7.2136	8mm
7 x 64 Bren	0.284	7.2136	8mm
7 mm Rem/ M	0.284	7.2136	8mm
308 Win	0.308	7.8232	9mm
.30-06 Spring	0.308	7.8232	9mm
.30-06 Ackley	0.308	7.8232	9mm
300 Win/ M	0.308	7.8232	9mm
300 H&H	0.308	7.8232	9mm
.308 Nor/ M	0.308	7.8232	9mm
.303 Brit	0.311	7.8994	9mm